



Matching Grant End-User Product List* in CHF dd 09 October 2009

* Please note that the List Prices in this Product list are only indicative. Refer to Sun's Price List to check the correct prices on the MG Request Data.
* End-User MG Prices are Recommended End-User Prices as Sun recommends them for the Matching Grant Program only.

Part Number	Description	Qty	MG Dis-count	List Price per part #	End-User MG Price* per part #	Last Order Date Soon?
Buy 1 / Get 1 "Free"™						
THIN CLIENTS						
Sun Ray Thin Client Product: PTO Configurations						
NTC-15Z-00	Sun Ray 2FS client, 1920 x 1200 max resolution, two DVI ports for native dual-head configurations in Xinerama mode, one 100Base-FX fiber optic port, 3 USB 2.0 ports, 1 serial port, RoHS-6 compliant. Type 7 country kit not included.	2	50%	SFr. 700	SFr. 350	No
NTC-20Z-00	Sun Ray 270 client, 4 USB 1.1 ports, 2 serial ports, 17 inch flat screen monitor, 1280x1024 max resolution, RoHS-6 compliant, Type 7 country kit not included.	2	50%	SFr. 980	SFr. 490	No
WORKSTATIONS						
Ultra 27: ATO Configuration Bundle 1						
B27-AA	Sun Ultra 27 Workstation Base Chassis; includes motherboard, PSU, no optical disk drive, no hard disk drive, RoHS-5. Media and Documentation Kit (Installation Guide, Tools & Drivers CD, Sun Installation Assistant CD, SMI SW Licensing Agreement)	2	50%	SFr. 900	SFr. 450	No
3912A	Intel Xeon Processor 3540 (2.93 GHz, Quad-Core, 4.8 GT/s QuickPath Interconnect, 1066MHz DDR3 memory controller, 8MB L3 cache, HyperThreading-enabled, Intel Turbo Boost-enabled, 130W TDP)	2	50%	SFr. 1'150	SFr. 575	No
3914A	ATO 1 x 2 GB DDR3-1333MHz Unbuffered DIMM for Sun Ultra 27 Workstation, RoHS-5 Compliant	6	50%	SFr. 168	SFr. 84	No
3918A	ATO NVIDIA Quadro FX 3800 Graphics Card. RoHS-5 Compliant	2	50%	SFr. 1'390	SFr. 695	No
4133A-Z	ATO Option DVD Dual for Sun Ultra 24 & Ultra 27 Workstation. 16X DVD+/-RW Drive supports read/write in dual +/- formats. Supports double-layer DVD to hold up to 8.5GB or single-layer DVD to hold up to 4.7GB. SATA. RoHS-6.	2	50%	SFr. 128	SFr. 64	No
8015A-Z	DVI-to-VGA Adapter. RoHS-6	2	50%	SFr. 17	SFr. 9	No
RB-ST1CE-500G7K	Internal 500GB 7200 rpm 3.5-inch Serial ATA Hard Disk Drive with bracket. RoHS-6. For XATO or Factory Integration only.	4	50%	SFr. 460	SFr. 230	No
SG-PCIE4SAS3-Z	4 x1 4-Port SAS PCI-E HBA Internal connection LSI3041E with B3 silicon. ATO Option. RoHS-6 compliant.	2	50%	SFr. 280	SFr. 140	No
ENTRY LEVEL SERVERS						
Sun Fire X2200 M2: ATO Configuration Bundle 1						
A85-A-QC	Sun Fire X2200 M2 x64 Server XATO Base Quad Core System: Chassis, Motherboard, 2x processor slots, 16x memory DIMM slots, 2x Serial ATA disk bays, 1x DVD bay, 1x AC PSU, Service Processor, 4x 10/100/1000 Ethernet ports, 6x USB 2.0 ports, No riser card assembly, no power cord, order Geo-specific X-option. Includes 1 MB flash rom required for Quad Core processors. RoHS-5. XATO and Factory Integration.	2	50%	SFr. 870	SFr. 435	01JAN10
4087A	8 GB Memory kit DDR2-667 Registered ECC DIMMs (2x4GB) for Sun Fire X2200 M2 x64 servers. RoHS-6. For XATO and Factory Integration.	4	50%	SFr. 810	SFr. 405	01JAN10
5294A-Z	DVD-ROM drive for Sun Fire X2100 M2 and Sun Fire X2200 M2 x64 servers. RoHS-5. For XATO & Factory Integration.	2	50%	SFr. 110	SFr. 55	01JAN10
RB-ST1CE-500G7K	Internal 500GB 7200 rpm 3.5-inch Serial ATA Hard Disk Drive with bracket. RoHS-6. For XATO or Factory Integration only.	4	50%	SFr. 460	SFr. 230	No
5334A	AMD Opteron Model 2376 (2.3GHz 6MB L3) 75W ACP Quad-Core Processor for Sun Fire X2200 M2 x64 servers. RoHS-5. For XATO and Factory Integration.	4	50%	SFr. 250	SFr. 125	01JAN10
8029A-Z	Slide rail kit for Sun Fire X2100, Sun Fire X2100 M2, Sun Fire X2200 M2, Sun Fire X4100, Sun Fire X4100 M2, Sun Fire X4200 and Sun Fire X4200 M2 x64 servers. Only fits in Sun Rack 900-38, Sun Rack 1000-38, Sun Rack 1000-42, or racks that have front-rear rail spacing between 610mm to 915mm (about 24" to about 36"). RoHS-6. For XATO and Factory Integration.	2	50%	SFr. 174	SFr. 87	No
Sun Fire X2200 M2: ATO Configuration Bundle 2						
A85-A-QC	Sun Fire X2200 M2 x64 Server XATO Base Quad Core System: Chassis, Motherboard, 2x processor slots, 16x memory DIMM slots, 2x Serial ATA disk bays, 1x DVD bay, 1x AC PSU, Service Processor, 4x 10/100/1000 Ethernet ports, 6x USB 2.0 ports, No riser card assembly, no power cord, order Geo-specific X-option. Includes 1 MB flash rom required for Quad Core processors. RoHS-5. XATO and Factory Integration.	2	50%	SFr. 870	SFr. 435	01JAN10
4087A	8 GB Memory kit DDR2-667 Registered ECC DIMMs (2x4GB) for Sun Fire X2200 M2 x64 servers. RoHS-6. For XATO and Factory Integration.	4	50%	SFr. 810	SFr. 405	01JAN10
5294A-Z	DVD-ROM drive for Sun Fire X2100 M2 and Sun Fire X2200 M2 x64 servers. RoHS-5. For XATO & Factory Integration.	2	50%	SFr. 110	SFr. 55	01JAN10
RB-ST1CE-500G7K	Internal 500GB 7200 rpm 3.5-inch Serial ATA Hard Disk Drive with bracket. RoHS-6. For XATO or Factory Integration only.	2	50%	SFr. 460	SFr. 230	No
5335A	AMD Opteron Model 2384 (2.7GHz 6MB L3) 75W ACP Quad-Core Processor for Sun Fire X2200 M2 x64 servers. RoHS-5. For XATO and Factory Integration.	4	50%	SFr. 930	SFr. 465	01JAN10
8029A-Z	Slide rail kit for Sun Fire X2100, Sun Fire X2100 M2, Sun Fire X2200 M2, Sun Fire X4100, Sun Fire X4100 M2, Sun Fire X4200 and Sun Fire X4200 M2 x64 servers. Only fits in Sun Rack 900-38, Sun Rack 1000-38, Sun Rack 1000-42, or racks that have front-rear rail spacing between 610mm to 915mm (about 24" to about 36"). RoHS-6. For XATO and Factory Integration.	2	50%	SFr. 174	SFr. 87	No
Sun Fire X2200 M2: ATO Configuration Bundle 3						
A85-A-QC	Sun Fire X2200 M2 x64 Server XATO Base Quad Core System: Chassis, Motherboard, 2x processor slots, 16x memory DIMM slots, 2x Serial ATA disk bays, 1x DVD bay, 1x AC PSU, Service Processor, 4x 10/100/1000 Ethernet ports, 6x USB 2.0 ports, No riser card assembly, no power cord, order Geo-specific X-option. Includes 1 MB flash rom required for Quad Core processors. RoHS-5. XATO and Factory Integration.	2	50%	SFr. 870	SFr. 435	01JAN10
5288A-C	4-GB Memory Kit (2x 2GB Registered ECC single rank DDR2-667) for Sun Fire X2200 M2 server. RoHS-6. For XATO and Factory Integration.	8	50%	SFr. 300	SFr. 150	01JAN10
5294A-Z	DVD-ROM drive for Sun Fire X2100 M2 and Sun Fire X2200 M2 x64 servers. RoHS-5. For XATO & Factory Integration.	2	50%	SFr. 110	SFr. 55	01JAN10

Part Number	Description	Qty	MG Dis-count	List Price per part #	End-User MG Price* per part #	Last Order Date Soon?
RB-ST1CE-500G7K	Internal 500GB 7200 rpm 3.5-inch Serial ATA Hard Disk Drive with bracket. RoHS-6. For XATO or Factory Integration only.	2	50%	SFr. 460	SFr. 230	No
5336A	AMD Opteron Model 2389 (2.9GHz 6MB L3) 75W ACP Quad-Core Processor for Sun Fire X2200 M2 x64 servers. RoHS-5. For XATO and Factory Integration.	4	50%	SFr. 1'280	SFr. 640	01JAN10
8029A-Z	Slide rail kit for Sun Fire X2100, Sun Fire X2100 M2, Sun Fire X2200 M2, Sun Fire X4100, Sun Fire X4100 M2, Sun Fire X4200 and Sun Fire X4200 M2 x64 servers. Only fits in Sun Rack 900-38, Sun Rack 1000-38, Sun Rack 1000-42, or racks that have front-rear rail spacing between 610mm to 915mm (about 24" to about 36"). RoHS-6. For XATO and Factory Integration.	2	50%	SFr. 174	SFr. 87	No
Sun Fire X2200 M2: Options						
4087A	8 GB Memory kit DDR2-667 Registered ECC DIMMs (2x4GB) for Sun Fire X2200 M2 x64 servers. RoHS-6. For XATO and Factory Integration.	2	50%	SFr. 810	SFr. 405	01JAN10
5288A-C	4-GB Memory Kit (2x 2GB Registered ECC single rank DDR2-667) for Sun Fire X2200 M2 server. RoHS-6. For XATO and Factory Integration.	2	50%	SFr. 300	SFr. 150	01JAN10
RB-SS1CE-300G15K	RoHS-6. Internal 300GB 15000 rpm 3.5-inch SAS HDD. XATO & factory integration.	2	50%	SFr. 1'090	SFr. 545	No
RB-SS1CE-146G15KZ	RoHS-6. Internal 146GB 15K SAS HDD, 3.5" x 1" drive. XATO & factory integration.	2	50%	SFr. 540	SFr. 270	No
RC-ST1CE-250G7K	Internal 250GB 7,200 RPM 3.5-inch Serial ATA Hard Disk Drive with bracket. RoHS-6. For XATO or Factory Integration only.	2	50%	SFr. 220	SFr. 110	18DEC09
RB-ST1CE-500G7K	Internal 500GB 7200 rpm 3.5-inch Serial ATA Hard Disk Drive with bracket. RoHS-6. For XATO or Factory Integration only.	2	50%	SFr. 460	SFr. 230	No
Sun Fire X2250: ATO Configuration Bundle 1						
X2250-H1-AA	Sun Fire X2250 Base Chassis; includes motherboard, PSU, AST2000 Service Processor (SP) integrated on motherboard for ILOM & VGA; no optical disk drive, no hard disk drive, RoHS-5. Media and Documentation Kit (Installation Guide, Tools & Drivers CD, Sun Installation Assistant CD, SMI SW Licensing Agreement) sold separately	2	50%	SFr. 930	SFr. 465	04DEC09
6381A	4GB Memory Kit with 2x2GB PC2-5300 667 MHz ECC Fully Buffered DDR2 DIMM. RoHS-6. XATO.	4	50%	SFr. 300	SFr. 150	No
5294A-Z	DVD-ROM drive for Sun Fire X2100 M2 and Sun Fire X2200 M2 x64 servers. RoHS-5. For XATO & Factory Integration.	2	50%	SFr. 110	SFr. 55	01JAN10
RB-ST1CE-1T7K	Internal 1TB 7200 rpm 3.5-inch Serial ATA Hard Disk Drive with bracket. RoHS-6. For XATO or Factory Integration only.	4	50%	SFr. 980	SFr. 490	No
5109A	Intel Xeon E5405 Quad Core (6MB L2, 2.0 GHz, 1333 MHz FSB, 80W)	4	50%	SFr. 410	SFr. 205	04DEC09
8029A-Z	Slide rail kit for Sun Fire X2100, Sun Fire X2100 M2, Sun Fire X2200 M2, Sun Fire X4100, Sun Fire X4100 M2, Sun Fire X4200 and Sun Fire X4200 M2 x64 servers. Only fits in Sun Rack 900-38, Sun Rack 1000-38, Sun Rack 1000-42, or racks that have front-rear rail spacing between 610mm to 915mm (about 24" to about 36"). RoHS-6. For XATO and Factory Integration.	2	50%	SFr. 174	SFr. 87	No
Sun Fire X2250: ATO Configuration Bundle 2						
X2250-H1-AA	Sun Fire X2250 Base Chassis; includes motherboard, PSU, AST2000 Service Processor (SP) integrated on motherboard for ILOM & VGA; no optical disk drive, no hard disk drive, RoHS-5. Media and Documentation Kit (Installation Guide, Tools & Drivers CD, Sun Installation Assistant CD, SMI SW Licensing Agreement) sold separately	2	50%	SFr. 930	SFr. 465	04DEC09
6382A	8GB Memory Kit with 2x4GB PC2-5300 667 MHz ECC Fully Buffered DDR2 DIMM for Sun Fire and Netra X4150, X4250 and X4450. RoHS-6. XATO.	4	50%	SFr. 590	SFr. 295	No
5294A-Z	DVD-ROM drive for Sun Fire X2100 M2 and Sun Fire X2200 M2 x64 servers. RoHS-5. For XATO & Factory Integration.	2	50%	SFr. 110	SFr. 55	01JAN10
RB-ST1CE-1T7K	Internal 1TB 7200 rpm 3.5-inch Serial ATA Hard Disk Drive with bracket. RoHS-6. For XATO or Factory Integration only.	4	50%	SFr. 980	SFr. 490	No
5109A	Intel Xeon E5405 Quad Core (6MB L2, 2.0 GHz, 1333 MHz FSB, 80W)	4	50%	SFr. 410	SFr. 205	04DEC09
8029A-Z	Slide rail kit for Sun Fire X2100, Sun Fire X2100 M2, Sun Fire X2200 M2, Sun Fire X4100, Sun Fire X4100 M2, Sun Fire X4200 and Sun Fire X4200 M2 x64 servers. Only fits in Sun Rack 900-38, Sun Rack 1000-38, Sun Rack 1000-42, or racks that have front-rear rail spacing between 610mm to 915mm (about 24" to about 36"). RoHS-6. For XATO and Factory Integration.	2	50%	SFr. 174	SFr. 87	No
Sun Fire X2250: ATO Configuration Bundle 3						
X2250-H1-AA	Sun Fire X2250 Base Chassis; includes motherboard, PSU, AST2000 Service Processor (SP) integrated on motherboard for ILOM & VGA; no optical disk drive, no hard disk drive, RoHS-5. Media and Documentation Kit (Installation Guide, Tools & Drivers CD, Sun Installation Assistant CD, SMI SW Licensing Agreement) sold separately	2	50%	SFr. 930	SFr. 465	04DEC09
6382A	8GB Memory Kit with 2x4GB PC2-5300 667 MHz ECC Fully Buffered DDR2 DIMM for Sun Fire and Netra X4150, X4250 and X4450. RoHS-6. XATO.	8	50%	SFr. 590	SFr. 295	No
5294A-Z	DVD-ROM drive for Sun Fire X2100 M2 and Sun Fire X2200 M2 x64 servers. RoHS-5. For XATO & Factory Integration.	2	50%	SFr. 110	SFr. 55	01JAN10
RB-ST1CE-1T7K	Internal 1TB 7200 rpm 3.5-inch Serial ATA Hard Disk Drive with bracket. RoHS-6. For XATO or Factory Integration only.	4	50%	SFr. 980	SFr. 490	No
5113A	Sun Fire X2250 Quad Core Intel Xeon Processor Model L5420 (2.50GHz, 1333MHz, 50W), ROHS-5.	4	50%	SFr. 710	SFr. 355	04DEC09
8029A-Z	Slide rail kit for Sun Fire X2100, Sun Fire X2100 M2, Sun Fire X2200 M2, Sun Fire X4100, Sun Fire X4100 M2, Sun Fire X4200 and Sun Fire X4200 M2 x64 servers. Only fits in Sun Rack 900-38, Sun Rack 1000-38, Sun Rack 1000-42, or racks that have front-rear rail spacing between 610mm to 915mm (about 24" to about 36"). RoHS-6. For XATO and Factory Integration.	2	50%	SFr. 174	SFr. 87	No
Sun Fire X2250: Options						
6381A	4GB Memory Kit with 2x2GB PC2-5300 667 MHz ECC Fully Buffered DDR2 DIMM. RoHS-6. XATO.	2	50%	SFr. 300	SFr. 150	No
6382A	8GB Memory Kit with 2x4GB PC2-5300 667 MHz ECC Fully Buffered DDR2 DIMM for Sun Fire and Netra X4150, X4250 and X4450. RoHS-6. XATO.	2	50%	SFr. 590	SFr. 295	No
Sun Fire X2270: ATO Configuration Bundle 1						
X2270-H1-AA	Sun Fire X2270 Server, ATO base chassis package including motherboard, 1 x PSU, No HDD, No Service Processor, RoHS-5 Compliant	2	50%	SFr. 1'150	SFr. 575	No
8337A	2 GB (1 x 2 GB DIMMs) DDR3-1333 Registered ECC Memory, for Sun Fire X2270 Server, RoHS-5 Compliant	6	50%	SFr. 181	SFr. 91	No
8340A	Sun Integrated Lights Out Management (ILOM) Service Processor Module, AST2100 on a mezzanine card option for Sun Fire X2270 Server	2	50%	SFr. 115	SFr. 58	No
8341A	Hot-Pluggable Disk bay filler panel for Sun Fire X2270 Server, RoHS-6 Compliant	4	50%	SFr. 0	SFr. 0	No
RA-ST1CR-1T7K	1TB 7.2K RPM, 3.5 inch SATA HDD with coral bracket. RoHS-6. ATO.	8	50%	SFr. 980	SFr. 490	No

Part Number	Description	Qty	MG Dis-count	List Price per part #	End-User MG Price* per part #	Last Order Date Soon?
8331A	2.00 GHz Intel Xeon E5504 with 4 MB Cache, 4.8 GT/s QPI, DDR3-800, Turbo Off, HT Off, 80W, for Sun Fire X2270 Server, RoHS-5 Compliant	2	50%	SFr. 350	SFr. 175	No
8348A	Slide Rail Kit for Sun Fire X2270 Server, RoHS-6 Compliant	2	50%	SFr. 174	SFr. 87	No
Sun Fire X4140: ATO Configuration Bundle 1						
B12-AA	Sun Fire X4140 x64 Server: XATO base chassis package including motherboard, no DVD, no PSU, redundant fans and Service Processor. RoHS-5.	2	50%	SFr. 1'890	SFr. 945	No
4285A	Hyper-Transport Bridge Card. Used for Two Quad or Six-Core Processor Configurations for the Sun Fire X4140, X4240 and X4440. Not Used Within A Four Processor Sun Fire X4440 Configuration. RoHS-6. XATO.	2	50%	SFr. 58	SFr. 29	No
6327A	Redundant hot-swappable AC 650W power supply unit for Sun Fire X4140 and X4150 x64 servers. XATO. RoHS-5.	4	50%	SFr. 290	SFr. 145	No
6322A	8 GB Memory kit DDR2-667 Registered ECC DIMMs (2x 4GB) for Sun Fire X4140/X4240/X4440 x64 servers. RoHS-5. XATO.	8	50%	SFr. 540	SFr. 270	No
6323A	DVD+/-RW drive for Sun Fire X4150/X4250/X4450/X4140/X4240/X4440 server. RoHS-5.	2	50%	SFr. 168	SFr. 84	No
4280A	Internal HBA Drive Cable Kit for Sun Fire X4140 server. XATO. ROHS-6.	2	50%	SFr. 0	SFr. 0	No
SG-PCIE8SAS-I-Z	Sun StorageTek (TM) 8-Port internal SAS PCI-Express LSI 3081E Host Bus Adapter with RAID 0, 1, 1E support. RoHS-6. XATO.	2	50%	SFr. 350	SFr. 175	No
SG-PCIESAS-R-INT-Z	Sun StorageTek (TM) 8-port internal SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256 MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. XATO.	2	50%	SFr. 840	SFr. 420	No
6331A	Drive bay filler panel for Sun Fire X4140/X4170/X4240/X4270/X4440/X4150 /X4450/Sun Blade X6270 x64 servers. RoHS-6. XATO.	8	50%	SFr. 0	SFr. 0	No
RA-SS2CD-300G10K	300GB 10K RPM 2.5" SAS hard disk drive with Nemo bracket. Factory Integrated. RoHS-6.	8	50%	SFr. 1'010	SFr. 505	No
5380A	2.1GHz AMD Opteron Model 2425 HE with 3MB L2, 6MB L3, 6-core for Sun Fire X4140 and X4240 Servers, RoHS-5 Compliant	4	50%	SFr. 790	SFr. 395	No
6326A	Slide rail kit for Sun Fire X4140/X4170/X4240/X4270/X4440/X4150 /X4450 server. Only fits in Sun Rack 938, Sun Rack 1038, Sun Rack 1042, or racks that have front to rear rail spacing between 610mm and 915mm (about 24" to about 36"). RoHS-6. XATO.	2	50%	SFr. 174	SFr. 87	No
Sun Fire X4140: ATO Configuration Bundle 2						
B12-AA	Sun Fire X4140 x64 Server: XATO base chassis package including motherboard, no DVD, no PSU, redundant fans and Service Processor. RoHS-5.	2	50%	SFr. 1'890	SFr. 945	No
4285A	Hyper-Transport Bridge Card. Used for Two Quad or Six-Core Processor Configurations for the Sun Fire X4140, X4240 and X4440. Not Used Within A Four Processor Sun Fire X4440 Configuration. RoHS-6. XATO.	2	50%	SFr. 58	SFr. 29	No
6327A	Redundant hot-swappable AC 650W power supply unit for Sun Fire X4140 and X4150 x64 servers. XATO. RoHS-5.	4	50%	SFr. 290	SFr. 145	No
6322A	8 GB Memory kit DDR2-667 Registered ECC DIMMs (2x 4GB) for Sun Fire X4140/X4240/X4440 x64 servers. RoHS-5. XATO.	16	50%	SFr. 540	SFr. 270	No
6323A	DVD+/-RW drive for Sun Fire X4150/X4250/X4450/X4140/X4240/X4440 server. RoHS-5.	2	50%	SFr. 168	SFr. 84	No
4280A	Internal HBA Drive Cable Kit for Sun Fire X4140 server. XATO. ROHS-6.	2	50%	SFr. 0	SFr. 0	No
SG-PCIE8SAS-I-Z	Sun StorageTek (TM) 8-Port internal SAS PCI-Express LSI 3081E Host Bus Adapter with RAID 0, 1, 1E support. RoHS-6. XATO.	2	50%	SFr. 350	SFr. 175	No
SG-PCIESAS-R-INT-Z	Sun StorageTek (TM) 8-port internal SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256 MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. XATO.	2	50%	SFr. 840	SFr. 420	No
6331A	Drive bay filler panel for Sun Fire X4140/X4170/X4240/X4270/X4440/X4150 /X4450/Sun Blade X6270 x64 servers. RoHS-6. XATO.	8	50%	SFr. 0	SFr. 0	No
RA-SS2CD-300G10K	300GB 10K RPM 2.5" SAS hard disk drive with Nemo bracket. Factory Integrated. RoHS-6.	8	50%	SFr. 1'010	SFr. 505	No
5392A	2.2GHz AMD Opteron Model 2427 with 3MB L2, 6MB L3, 6-core for Sun Fire X4140 and X4240 Servers, RoHS-5 Compliant	4	50%	SFr. 700	SFr. 350	No
6326A	Slide rail kit for Sun Fire X4140/X4170/X4240/X4270/X4440/X4150 /X4450 server. Only fits in Sun Rack 938, Sun Rack 1038, Sun Rack 1042, or racks that have front to rear rail spacing between 610mm and 915mm (about 24" to about 36"). RoHS-6. XATO.	2	50%	SFr. 174	SFr. 87	No
Sun Fire X4150: ATO Configuration Bundle 1						
B13-BA	Sun Fire X4150 x64 Rack-Mount Server 1U base chassis including ILOM, 4x 10/100/1000 Ethernet ports, 5x USB 2.0 ports and 1x AC power supply. This system can support up to 2 Intel Xeon processors, 16 memory DIMMs, 1 SATA-based DVD drive, 8 disk drives, 3 PCI-Express cards and a second AC power supply unit. RoHS-5. ATO.	2	50%	SFr. 1'970	SFr. 985	01JAN10
6327A	Redundant hot-swappable AC 650W power supply unit for Sun Fire X4140 and X4150 x64 servers. XATO. RoHS-5.	2	50%	SFr. 290	SFr. 145	No
6381A	4GB Memory Kit with 2x2GB PC2-5300 667 MHz ECC Fully Buffered DDR2 DIMM. RoHS-6. XATO.	4	50%	SFr. 300	SFr. 150	No
6323A	DVD+/-RW drive for Sun Fire X4150/X4250/X4450/X4140/X4240/X4440 server. RoHS-5.	2	50%	SFr. 168	SFr. 84	No
6388A	Internal SAS Drive Cable Kit for Sun Fire X4150 server. ROHS-5. XATO.	2	50%	SFr. 17	SFr. 9	01JAN10
RA-SS2CF-300G10K	300GB 10K RPM 2.5" SAS hard disk drive with Marlin bracket. Factory Integrated. RoHS-6	8	50%	SFr. 1'010	SFr. 505	No
SG-PCIESAS-R-INT-Z	Sun StorageTek (TM) 8-port internal SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256 MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. XATO.	2	50%	SFr. 840	SFr. 420	No
6391A	Quad-Core Intel(R) Xeon(R) E5410 processor (2x6MB L2, 2.33 GHz, 1333 MHz FSB, 80W) for Sun Fire X4150 and X4250 server. RoHS-5. XATO.	4	50%	SFr. 520	SFr. 260	01JAN10
6326A	Slide rail kit for Sun Fire X4140/X4170/X4240/X4270/X4440/X4150 /X4450 server. Only fits in Sun Rack 938, Sun Rack 1038, Sun Rack 1042, or racks that have front to rear rail spacing between 610mm and 915mm (about 24" to about 36"). RoHS-6. XATO.	2	50%	SFr. 174	SFr. 87	No
Sun Fire X4170: ATO Configuration Bundle 1						
X4170-S1-AA	Sun Fire X4170 x64 Server: Base chassis package including motherboard, no DVD, 1 x PSU, redundant fans and Service Processor for Factory Integration. RoHS-6.	2	50%	SFr. 2'450	SFr. 1'225	No
5872A	Redundant hot-swappable AC 760W power supply unit for Sun Fire X4170 x64 servers. Factory Integration Only. RoHS-6.	2	50%	SFr. 290	SFr. 145	No
5867A	4 GB Memory kit DDR3-1066 Registered ECC DIMMs (1 x 4 GB) for Sun Fire X4170, X4270 & X4275 x64 servers. RoHS-6. For Factory Integration Only.	12	50%	SFr. 340	SFr. 170	No
5879A	Memory Filler Panel for Sun Fire X4170 and X4270; Sun Blade X6275 Server Module, Sun Blade X6270 Server Module. For Factory Integration Only. RoHS-6.	12	50%	SFr. 0	SFr. 0	No
8325A	DVD+/-RW SATA-based drive for Sun Fire X4170/X4270 x64 servers. RoHS-5. XATO.	2	50%	SFr. 168	SFr. 84	No

Part Number	Description	Qty	MG Dis-count	List Price per part #	End-User MG Price* per part #	Last Order Date Soon?
6331A	Drive bay filler panel for Sun Fire X4140/X4170/X4240/X4270/X4440/X4150 /X4450/Sun Blade X6270 x64 servers. RoHS-6. XATO.	12	50%	SFr. 0	SFr. 0	No
RA-SS1CR-300G15K	300GB 15K RPM, 3.5 inch SAS HDD with coral bracket, ROHS 6, For Factory Integration Only	16	50%	SFr. 1'090	SFr. 545	No
SG-PCIESAS-R-INT-Z	Sun StorageTek (TM) 8-port internal SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256 MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. XATO.	2	50%	SFr. 840	SFr. 420	No
5865A	1 Intel Xeon Model Number E5520 Quad-Core (2.26GHz/80W) Processor without Heatsink for Sun Fire X4170 & Sun Fire X4270 & Sun Fire X4275 Servers. RoHS-6. For Factory Integration Only.	4	50%	SFr. 630	SFr. 315	No
5898A	CPU Heatsink for Sun Fire X4170 Server. For Factory Integration Only. RoHS-6.	4	50%	SFr. 0	SFr. 0	No
6326A	Slide rail kit for Sun Fire X4140/X4170/X4240/X4270/X4440/X4150 /X4450 server. Only fits in Sun Rack 938, Sun Rack 1038, Sun Rack 1042, or racks that have front to rear rail spacing between 610mm and 915mm (about 24" to about 36"). RoHS-6. XATO.	2	50%	SFr. 174	SFr. 87	No
Sun Fire X4240: ATO Configuration Bundle 1						
B14-AB	Sun Fire X4240 x64 Server: XATO base chassis package including motherboard, no DVD, no PSU, redundant fans and Service Processor. Needed for AMD Opteron 2300 Series SE Processors. RoHS-5.	2	50%	SFr. 2'520	SFr. 1'260	No
4285A	Hyper-Transport Bridge Card. Used for Two Quad or Six-Core Processor Configurations for the Sun Fire X4140, X4240 and X4440. Not Used Within A Four Processor Sun Fire X4440 Configuration. RoHS-6. XATO.	2	50%	SFr. 58	SFr. 29	No
6328A	Redundant hot-swappable AC 1050W power supply unit for Sun Fire X4240/X4270/X4275/X4440/X4450 x64 servers. XATO. RoHS-5.	4	50%	SFr. 290	SFr. 145	No
6321A-C	4 GB Memory kit DDR2-667 Registered ECC single rank DIMMs (2x 2GB) for Sun Fire X4140/X4240/X4440 x64 servers. RoHS-5.	4	50%	SFr. 300	SFr. 150	No
6383A	Two Memory slot filler panels for Sun Fire X4140/X4240/X4440/X4450 servers. XATO. RoHS-5.	24	50%	SFr. 0	SFr. 0	No
6323A	DVD+/-RW drive for Sun Fire X4150/X4250/X4450/X4140/X4240/X4440 server. RoHS-5.	2	50%	SFr. 168	SFr. 84	No
4282A	XATO Internal HBA Drive Cable Kit for Sun Fire X4240 and X4440 server. XATO. ROHS-6.	2	50%	SFr. 0	SFr. 0	No
RB-SS2CF-146G10K	146GB 10K RPM 2.5" SAS hard disk drive with Marlin bracket. RoHS-6. (ATO)	32	50%	SFr. 490	SFr. 245	No
SG-PCIESAS-R-INT-Z	Sun StorageTek (TM) 8-port internal SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256 MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. XATO.	2	50%	SFr. 840	SFr. 420	No
5380A	2.1GHz AMD Opteron Model 2425 HE with 3MB L2, 6MB L3, 6-core for Sun Fire X4140 and X4240 Servers. RoHS-5 Compliant	4	50%	SFr. 790	SFr. 395	No
6326A	Slide rail kit for Sun Fire X4140/X4170/X4240/X4270/X4440/X4150 /X4450 server. Only fits in Sun Rack 938, Sun Rack 1038, Sun Rack 1042, or racks that have front to rear rail spacing between 610mm and 915mm (about 24" to about 36"). RoHS-6. XATO.	2	50%	SFr. 174	SFr. 87	No
Sun Fire X4270: ATO Configuration Bundle 1						
X4270-S1-AA	Sun Fire X4270 x64 Server: 2.5-inch HDD base chassis package including motherboard, no DVD, 1 x PSU, redundant fans and Service Processor for Factory Integration. RoHS-6.	2	50%	SFr. 3'150	SFr. 1'575	No
6328A	Redundant hot-swappable AC 1050W power supply unit for Sun Fire X4240/X4270/X4275/X4440/X4450 x64 servers. XATO. RoHS-5.	4	50%	SFr. 290	SFr. 145	No
5867A	4 GB Memory kit DDR3-1066 Registered ECC DIMMs (1 x 4 GB) for Sun Fire X4170, X4270 & X4275 x64 servers. RoHS-6. For Factory Integration Only.	12	50%	SFr. 340	SFr. 170	No
5870A	4 GB Memory kit DDR3-1333 Registered ECC DIMMs (1 x 4 GB) for Sun Fire X4170, X4270 & X4275 x64 servers. RoHS-6. For Factory Integration Only.	0	50%	SFr. 350	SFr. 175	No
5879A	Memory Filler Panel for Sun Fire X4170 and X4270; Sun Blade X6275 Server Module, Sun Blade X6270 Server Module. For Factory Integration Only. RoHS-6.	24	50%	SFr. 0	SFr. 0	No
8325A	DVD+/-RW SATA-based drive for Sun Fire X4170/X4270 x64 servers. RoHS-5. XATO.	2	50%	SFr. 168	SFr. 84	No
6331A	Drive bay filler panel for Sun Fire X4140/X4170/X4240/X4270/X4440/X4150 /X4450/Sun Blade X6270 x64 servers. RoHS-6. XATO.	16	50%	SFr. 0	SFr. 0	No
RA-SS2CF-300G10K	300GB 10K RPM 2.5" SAS hard disk drive with Marlin bracket. Factory Integrated. RoHS-6	16	50%	SFr. 1'010	SFr. 505	No
SG-PCIESAS-R-INT-Z	Sun StorageTek (TM) 8-port internal SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256 MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. XATO.	2	50%	SFr. 840	SFr. 420	No
5865A	1 Intel Xeon Model Number E5520 Quad-Core (2.26GHz/80W) Processor without Heatsink for Sun Fire X4170 & Sun Fire X4270 & Sun Fire X4275 Servers. RoHS-6. For Factory Integration Only.	4	50%	SFr. 630	SFr. 315	No
5899A	CPU Heatsink for Sun Fire X4270 & X4275 Server. For Factory Integration Only. RoHS-6	4	50%	SFr. 0	SFr. 0	No
6326A	Slide rail kit for Sun Fire X4140/X4170/X4240/X4270/X4440/X4150 /X4450 server. Only fits in Sun Rack 938, Sun Rack 1038, Sun Rack 1042, or racks that have front to rear rail spacing between 610mm and 915mm (about 24" to about 36"). RoHS-6. XATO.	2	50%	SFr. 174	SFr. 87	No
Sun Fire X4270: ATO Configuration Bundle 2						
X4270-S1-AA	Sun Fire X4270 x64 Server: 2.5-inch HDD base chassis package including motherboard, no DVD, 1 x PSU, redundant fans and Service Processor for Factory Integration. RoHS-6.	2	50%	SFr. 3'150	SFr. 1'575	No
6328A	Redundant hot-swappable AC 1050W power supply unit for Sun Fire X4240/X4270/X4275/X4440/X4450 x64 servers. XATO. RoHS-5.	4	50%	SFr. 290	SFr. 145	No
5867A	4 GB Memory kit DDR3-1066 Registered ECC DIMMs (1 x 4 GB) for Sun Fire X4170, X4270 & X4275 x64 servers. RoHS-6. For Factory Integration Only.	12	50%	SFr. 340	SFr. 170	No
5879A	Memory Filler Panel for Sun Fire X4170 and X4270; Sun Blade X6275 Server Module, Sun Blade X6270 Server Module. For Factory Integration Only. RoHS-6.	24	50%	SFr. 0	SFr. 0	No
8325A	DVD+/-RW SATA-based drive for Sun Fire X4170/X4270 x64 servers. RoHS-5. XATO.	2	50%	SFr. 168	SFr. 84	No
6331A	Drive bay filler panel for Sun Fire X4140/X4170/X4240/X4270/X4440/X4150 /X4450/Sun Blade X6270 x64 servers. RoHS-6. XATO.	16	50%	SFr. 0	SFr. 0	No
RA-SS2CF-300G10K	300GB 10K RPM 2.5" SAS hard disk drive with Marlin bracket. Factory Integrated. RoHS-6	16	50%	SFr. 1'010	SFr. 505	No
SG-PCIESAS-R-INT-Z	Sun StorageTek (TM) 8-port internal SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256 MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. XATO.	2	50%	SFr. 840	SFr. 420	No
5864A	1 Intel Xeon L5520, 4C, 2.26 GHz, 60W, 8MB Cache, Intel Turbo Boost Technology, Intel HT Technology Processor without Heatsink for Sun Fire X4170, Sun Fire X4270 & Sun Fire X4275 Servers. RoHS-6 Compliant. For Factory Integration Only.	4	50%	SFr. 930	SFr. 465	No
5899A	CPU Heatsink for Sun Fire X4270 & X4275 Server. For Factory Integration Only. RoHS-6	4	50%	SFr. 0	SFr. 0	No
6326A	Slide rail kit for Sun Fire X4140/X4170/X4240/X4270/X4440/X4150 /X4450 server. Only fits in Sun Rack 938, Sun Rack 1038, Sun Rack 1042, or racks that have front to rear rail spacing between 610mm and 915mm (about 24" to about 36"). RoHS-6. XATO.	2	50%	SFr. 174	SFr. 87	No

Part Number	Description	Qty	MG Dis-count	List Price per part #	End-User MG Price* per part #	Last Order Date Soon?
Sun Fire X4270: ATO Configuration Bundle 3						
X4270-S1-AA	Sun Fire X4270 x64 Server: 2.5-inch HDD base chassis package including motherboard, no DVD, 1 x PSU, redundant fans and Service Processor for Factory Integration. RoHS-6.	2	50%	SFr. 3'150	SFr. 1'575	No
6328A	Redundant hot-swappable AC 1050W power supply unit for Sun Fire X4240/X4270/X4275/X4440/X4450 x64 servers. XATO. RoHS-5.	4	50%	SFr. 290	SFr. 145	No
5867A	4 GB Memory kit DDR3-1066 Registered ECC DIMMs (1 x 4 GB) for Sun Fire X4170, X4270 & X4275 x64 servers. RoHS-6. For Factory Integration Only.	12	50%	SFr. 340	SFr. 170	No
5879A	Memory Filler Panel for Sun Fire X4170 and X4270; Sun Blade X6275 Server Module, Sun Blade X6270 Server Module. For Factory Integration Only. RoHS-6.	24	50%	SFr. 0	SFr. 0	No
8325A	DVD+/-RW SATA-based drive for Sun Fire X4170/X4270 x64 servers. RoHS-5. XATO.	2	50%	SFr. 168	SFr. 84	No
6331A	Drive bay filler panel for Sun Fire X4140/X4170/X4240/X4270/X4440/X4150 /X4450/Sun Blade X6270 x64 servers. RoHS-6. XATO.	16	50%	SFr. 0	SFr. 0	No
RA-SS2CF-300G10K	300GB 10K RPM 2.5" SAS hard disk drive with Marlin bracket. Factory Integrated. RoHS-6	16	50%	SFr. 1'010	SFr. 505	No
SG-PCIESAS-R-INT-Z	Sun StorageTek (TM) 8-port internal SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256 MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. XATO.	2	50%	SFr. 840	SFr. 420	No
5863A	1 Intel Xeon E5540, 4C, 2.53 GHz, 80W, 8MB Cache, Intel Turbo Boost Technology, Intel HT Technology Processor without Heatsink for Sun Fire X4170, Sun Fire X4270 & Sun Fire X4275 Servers. RoHS-6 Compliant. For Factory Integration Only.	4	50%	SFr. 1'390	SFr. 695	No
5899A	CPU Heatsink for Sun Fire X4270 & X4275 Server. For Factory Integration Only. RoHS-6	4	50%	SFr. 0	SFr. 0	No
6326A	Slide rail kit for Sun Fire X4140/X4170/X4240/X4270/X4440/X4150 /X4450 server. Only fits in Sun Rack 938, Sun Rack 1038, Sun Rack 1042, or racks that have front to rear rail spacing between 610mm and 915mm (about 24" to about 36"). RoHS-6. XATO.	2	50%	SFr. 174	SFr. 87	No
Sun Fire X4270: ATO Configuration Bundle 4						
X4270-S1-AA	Sun Fire X4270 x64 Server: 2.5-inch HDD base chassis package including motherboard, no DVD, 1 x PSU, redundant fans and Service Processor for Factory Integration. RoHS-6.	2	50%	SFr. 3'150	SFr. 1'575	No
6328A	Redundant hot-swappable AC 1050W power supply unit for Sun Fire X4240/X4270/X4275/X4440/X4450 x64 servers. XATO. RoHS-5.	4	50%	SFr. 290	SFr. 145	No
5867A	4 GB Memory kit DDR3-1066 Registered ECC DIMMs (1 x 4 GB) for Sun Fire X4170, X4270 & X4275 x64 servers. RoHS-6. For Factory Integration Only.	12	50%	SFr. 340	SFr. 170	No
5879A	Memory Filler Panel for Sun Fire X4170 and X4270; Sun Blade X6275 Server Module, Sun Blade X6270 Server Module. For Factory Integration Only. RoHS-6.	24	50%	SFr. 0	SFr. 0	No
8325A	DVD+/-RW SATA-based drive for Sun Fire X4170/X4270 x64 servers. RoHS-5. XATO.	2	50%	SFr. 168	SFr. 84	No
6331A	Drive bay filler panel for Sun Fire X4140/X4170/X4240/X4270/X4440/X4150 /X4450/Sun Blade X6270 x64 servers. RoHS-6. XATO.	16	50%	SFr. 0	SFr. 0	No
RA-SS2CF-300G10K	300GB 10K RPM 2.5" SAS hard disk drive with Marlin bracket. Factory Integrated. RoHS-6	20	50%	SFr. 1'010	SFr. 505	No
SG-PCIESAS-R-INT-Z	Sun StorageTek (TM) 8-port internal SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256 MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. XATO.	2	50%	SFr. 840	SFr. 420	No
5862A	1 Intel Xeon Model Number X5560 Quad-Core (2.8GHz/95W) Processor without Heatsink for Sun Fire X4170 & Sun Fire X4270 & Sun Fire X4275 Servers. For Factory Integration Only.	4	50%	SFr. 2'050	SFr. 1'025	No
5899A	CPU Heatsink for Sun Fire X4270 & X4275 Server. For Factory Integration Only. RoHS-6	4	50%	SFr. 0	SFr. 0	No
6326A	Slide rail kit for Sun Fire X4140/X4170/X4240/X4270/X4440/X4150 /X4450 server. Only fits in Sun Rack 938, Sun Rack 1038, Sun Rack 1042, or racks that have front to rear rail spacing between 610mm and 915mm (about 24" to about 36"). RoHS-6. XATO.	2	50%	SFr. 174	SFr. 87	No
Sun Fire X4275: ATO Configuration Bundle 1						
X4275-S1-AA	Sun Fire X4275 x64 Server: 3.5-inch HDD base chassis package including motherboard, no DVD, 1xPSU, redundant fans and Service Processor. RoHS-6. For Factory Integration Only.	2	50%	SFr. 3'390	SFr. 1'695	No
6328A	Redundant hot-swappable AC 1050W power supply unit for Sun Fire X4240/X4270/X4275/X4440/X4450 x64 servers. XATO. RoHS-5.	4	50%	SFr. 290	SFr. 145	No
5867A	4 GB Memory kit DDR3-1066 Registered ECC DIMMs (1 x 4 GB) for Sun Fire X4170, X4270 & X4275 x64 servers. RoHS-6. For Factory Integration Only.	12	50%	SFr. 340	SFr. 170	No
5879A	Memory Filler Panel for Sun Fire X4170 and X4270; Sun Blade X6275 Server Module, Sun Blade X6270 Server Module. For Factory Integration Only. RoHS-6.	34	50%	SFr. 0	SFr. 0	No
RA-SS1CR-300G15K	300GB 15K RPM, 3.5 inch SAS HDD with coral bracket, ROHS 6, For Factory Integration Only	16	50%	SFr. 1'090	SFr. 545	No
SG-PCIESAS-R-INT-Z	Sun StorageTek (TM) 8-port internal SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256 MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. XATO.	2	50%	SFr. 840	SFr. 420	No
5865A	1 Intel Xeon Model Number E5520 Quad-Core (2.26GHz/80W) Processor without Heatsink for Sun Fire X4170 & Sun Fire X4270 & Sun Fire X4275 Servers. RoHS-6. For Factory Integration Only.	4	50%	SFr. 630	SFr. 315	No
5899A	CPU Heatsink for Sun Fire X4270 & X4275 Server. For Factory Integration Only. RoHS-6	4	50%	SFr. 0	SFr. 0	No
5889A	Tool-less Slide Rail Kit for Sun Fire X4275 x64 servers. For Factory Integration Only. RoHS-6.	2	50%	SFr. 174	SFr. 87	No
Sun Fire X4275: ATO Configuration Bundle 2						
X4275-S1-AA	Sun Fire X4275 x64 Server: 3.5-inch HDD base chassis package including motherboard, no DVD, 1xPSU, redundant fans and Service Processor. RoHS-6. For Factory Integration Only.	2	50%	SFr. 3'390	SFr. 1'695	No
6328A	Redundant hot-swappable AC 1050W power supply unit for Sun Fire X4240/X4270/X4275/X4440/X4450 x64 servers. XATO. RoHS-5.	4	50%	SFr. 290	SFr. 145	No
5867A	4 GB Memory kit DDR3-1066 Registered ECC DIMMs (1 x 4 GB) for Sun Fire X4170, X4270 & X4275 x64 servers. RoHS-6. For Factory Integration Only.	12	50%	SFr. 340	SFr. 170	No
5879A	Memory Filler Panel for Sun Fire X4170 and X4270; Sun Blade X6275 Server Module, Sun Blade X6270 Server Module. For Factory Integration Only. RoHS-6.	34	50%	SFr. 0	SFr. 0	No
RA-SS1CR-300G15K	300GB 15K RPM, 3.5 inch SAS HDD with coral bracket, ROHS 6, For Factory Integration Only	16	50%	SFr. 1'090	SFr. 545	No
SG-PCIESAS-R-INT-Z	Sun StorageTek (TM) 8-port internal SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256 MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. XATO.	2	50%	SFr. 840	SFr. 420	No
5863A	1 Intel Xeon E5540, 4C, 2.53 GHz, 80W, 8MB Cache, Intel Turbo Boost Technology, Intel HT Technology Processor without Heatsink for Sun Fire X4170, Sun Fire X4270 & Sun Fire X4275 Servers. RoHS-6 Compliant. For Factory Integration Only.	4	50%	SFr. 1'390	SFr. 695	No
5899A	CPU Heatsink for Sun Fire X4270 & X4275 Server. For Factory Integration Only. RoHS-6	4	50%	SFr. 0	SFr. 0	No
5889A	Tool-less Slide Rail Kit for Sun Fire X4275 x64 servers. For Factory Integration Only. RoHS-6.	2	50%	SFr. 174	SFr. 87	No
Sun Fire X4275: ATO Configuration Bundle 3						

Part Number	Description	Qty	MG Dis-count	List Price per part #	End-User MG Price* per part #	Last Order Date Soon?
X4275-S1-AA	Sun Fire X4275 x64 Server: 3.5-inch HDD base chassis package including motherboard, no DVD, 1xPSU, redundant fans and Service Processor. RoHS-6. For Factory Integration Only.	2	50%	SFr. 3'390	SFr. 1'695	No
6328A	Redundant hot-swappable AC 1050W power supply unit for Sun Fire X4240/X4270/X4275/X4440/X4450 x64 servers. XATO. RoHS-5.	4	50%	SFr. 290	SFr. 145	No
5867A	4 GB Memory kit DDR3-1066 Registered ECC DIMMs (1 x 4 GB) for Sun Fire X4170, X4270 & X4275 x64 servers. RoHS-6. For Factory Integration Only.	12	50%	SFr. 340	SFr. 170	No
RA-SS1CR-300G15K	300GB 15K RPM, 3.5 inch SAS HDD with coral bracket, ROHS 6, For Factory Integration Only	16	50%	SFr. 1'090	SFr. 545	No
SG-PCIESAS-R-INT-Z	Sun StorageTek (TM) 8-port internal SAS RAID Host Bus Adapter with RAID 0, 1, 1E, 10, 5, 5EE, 50, 6, 60 support, 256 MB of onboard memory and 72 hour Battery Backed Write Cache. RoHS 6. XATO.	2	50%	SFr. 840	SFr. 420	No
5864A	1 Intel Xeon L5520, 4C, 2.26 GHz, 60W, 8MB Cache, Intel Turbo Boost Technology, Intel HT Technology Processor without Heatsink for Sun Fire X4170, Sun Fire X4270 & Sun Fire X4275 Servers. RoHS-6 Compliant. For Factory Integration Only.	4	50%	SFr. 930	SFr. 465	No
5899A	CPU Heatsink for Sun Fire X4270 & X4275 Server. For Factory Integration Only. RoHS-6	4	50%	SFr. 0	SFr. 0	No
5889A	Tool-less Slide Rail Kit for Sun Fire X4275 x64 servers. For Factory Integration Only. RoHS-6.	2	50%	SFr. 174	SFr. 87	No
Sun Fire X4540: PTO Configuration						
B24-BZ2-32G-HMH	SF x4540 system with new Istanbul 6 core CPU, fully populated with 16 2GB Dimms, 48 500GB drives	2	50%	SFr. 34'650	SFr. 17'325	No
B24-BZ2-32G-SMH	SF x4540 system with new Istanbul 6 core CPU, fully populated with 16 2GB Dimms, 48 1000GB drives	2	50%	SFr. 55'600	SFr. 27'800	No
B24-FZZ2-64G-SMH	Sun Fire X4540 server, 2x AMD Opteron Model quad-core 2384, 2.7GHz Processor,16x4GB Mem, 48 SATA 3.5 1000GB, 7200RPM HDD, 2x PSU,support 110V with the 3rd PSU added, Service Processor, 4x 10/100/1000 Ethernet ports, 4x USB 2.0 ports, 3x PCI-E slots, VGA port, 1xflash boot disk slot, no power cord, order Geo-specific x-option. Solaris 10 OS preinstalled, includes Slide Rail Kit and Cable Management Arm, RoHS-5.	2	50%	SFr. 79'860	SFr. 39'930	No
Sun Fire X4600 M2: ATO Configuration Bundle 1						
A67-AVM2-1133	Sun Fire X4600 M2 XATO Base with 4x1133W power supplies, also includes DVD-RW drive and slide rail kit. Add processor modules, memory, disk, I/O cards. No power cord, must add Geo-specific power cord option RoHS-5. For XATO & Factory Integration.	2	50%	SFr. 5'670	SFr. 2'835	No
8098A	8 GB Memory kit DDR2-667 Registered ECC DIMMs (2x4 GB) for Sun Fire X4600 M2 x64 servers. RoHS-6. (FOR XATO and Factory Integration)	4	50%	SFr. 540	SFr. 270	No
8042A-Z	Disk bay filler panel for Sun Fire X4100, X4200, X4600 x64 servers, and X6250. XATO and Factory Integration. ROHS-5	4	50%	SFr. 0	SFr. 0	No
RB-SS2CD-146G10K	146GB 10K RPM 2.5" SAS hard disk drive with Nemo bracket. RoHS-6 Compliant. (ATO)	4	50%	SFr. 490	SFr. 245	No
8472A	X4600 M2 quad core processor board with 1 x 8376 HE (2.3 GHz Quad Core,55W) /8 DIMM. RoHS-5. (For XATO)	4	50%	SFr. 4'410	SFr. 2'205	No
Sun Fire X4600 M2: ATO Configuration Bundle 2						
A67-AVM2-1133	Sun Fire X4600 M2 XATO Base with 4x1133W power supplies, also includes DVD-RW drive and slide rail kit. Add processor modules, memory, disk, I/O cards. No power cord, must add Geo-specific power cord option RoHS-5. For XATO & Factory Integration.	2	50%	SFr. 5'670	SFr. 2'835	No
8123A-C-Z	4 GB Memory kit DDR2-667 Registered ECC single rank DIMMs (2x2 GB) for Sun Fire X4600 M2 x64 servers. RoHS-6. (FOR XATO and Factory Integration)	4	50%	SFr. 300	SFr. 150	No
8042A-Z	Disk bay filler panel for Sun Fire X4100, X4200, X4600 x64 servers, and X6250. XATO and Factory Integration. ROHS-5	4	50%	SFr. 0	SFr. 0	No
RB-SS2CD-146G10K	146GB 10K RPM 2.5" SAS hard disk drive with Nemo bracket. RoHS-6 Compliant. (ATO)	4	50%	SFr. 490	SFr. 245	No
8474A	X4600 M2 quad core processor board with 1 x 8380 (2.5 GHz Quad Core,75W) /8 DIMM. RoHS-5. (For XATO)	4	50%	SFr. 3'470	SFr. 1'735	No
Sun Fire X4600 M2: ATO Configuration Bundle 3						
A67-AVM2-1133	Sun Fire X4600 M2 XATO Base with 4x1133W power supplies, also includes DVD-RW drive and slide rail kit. Add processor modules, memory, disk, I/O cards. No power cord, must add Geo-specific power cord option RoHS-5. For XATO & Factory Integration.	2	50%	SFr. 5'670	SFr. 2'835	No
8098A	8 GB Memory kit DDR2-667 Registered ECC DIMMs (2x4 GB) for Sun Fire X4600 M2 x64 servers. RoHS-6. (FOR XATO and Factory Integration)	4	50%	SFr. 540	SFr. 270	No
8042A-Z	Disk bay filler panel for Sun Fire X4100, X4200, X4600 x64 servers, and X6250. XATO and Factory Integration. ROHS-5	4	50%	SFr. 0	SFr. 0	No
RB-SS2CD-146G10K	146GB 10K RPM 2.5" SAS hard disk drive with Nemo bracket. RoHS-6 Compliant. (ATO)	4	50%	SFr. 490	SFr. 245	No
8476A	X4600 M2 quad core processor board with 1 x 8384 (2.7 GHz Quad Core,75W) /8 DIMM. RoHS-5. (For XATO)	4	50%	SFr. 4'650	SFr. 2'325	No
Sun Fire X4600 M2: ATO Configuration Bundle 4						
A67-AVM2-1133	Sun Fire X4600 M2 XATO Base with 4x1133W power supplies, also includes DVD-RW drive and slide rail kit. Add processor modules, memory, disk, I/O cards. No power cord, must add Geo-specific power cord option RoHS-5. For XATO & Factory Integration.	2	50%	SFr. 5'670	SFr. 2'835	No
8098A	8 GB Memory kit DDR2-667 Registered ECC DIMMs (2x4 GB) for Sun Fire X4600 M2 x64 servers. RoHS-6. (FOR XATO and Factory Integration)	4	50%	SFr. 540	SFr. 270	No
8042A-Z	Disk bay filler panel for Sun Fire X4100, X4200, X4600 x64 servers, and X6250. XATO and Factory Integration. ROHS-5	4	50%	SFr. 0	SFr. 0	No
RB-SS2CD-146G10K	146GB 10K RPM 2.5" SAS hard disk drive with Nemo bracket. RoHS-6 Compliant. (ATO)	4	50%	SFr. 490	SFr. 245	No
8478A	2.9GHz Quad-Core AMD Opteron Model 8389 processor module with 512KB L1 Cache for Sun Fire X4600 M2. RoHS-5 compliant	4	50%	SFr. 5'750	SFr. 2'875	No
Sun Fire X4600 M2: PTO Configuration						
A67-ZWZ8-8H-064LB1	Sun Fire X4600 M2 x64 server: 8xAMD Opteron Model 8384 processor (2.7GHz-ACP75W-quad-core-8DIMM), 16x4GB DDR2-667 memory, 2x146 GB SAS drive, DVD-ROM, 4x1133W/ higher PSU, Service Processor, 4x10/100/1000 BaseT Ethernet ports, 4xUSB 2.0 ports, 2xPCI-X slots, 6x PCI-E slots(4x8-lane, 2x4-lane), and sliderail kit. No power cord, must order Geo-specific power cord option.RoHS-5. Standard Configuration.	2	50%	SFr. 43'950	SFr. 21'975	No
SUN SPARC ENTERPRISE SERVERS						
Sun Sparc Enterprise T5120 / T5220 Server: PTO Configurations						
SECPADF1Z	Sun SPARC Enterprise T5120 Server, 4 Core 1.2GHz UltraSPARC T2 processor, 2nd Generation Chassis, 8GB FBDIMM memory }(4 * 2GB), 2 * 146GB 10K RPM SAS disks, 1 SATA DVD+/-RW, 4 10/100/1000 Ethernet ports, 1 serial port, 4 USB ports,1 dedicated PCI-E low profile slot, 2 PCI-E low profile or XAUI (10Gb ethernet) slots, 2 (N+1) 720W power supplies, Solaris 10 pre-installed, RoHS-6 compliant.(Standard Configuration)	2	50%	SFr. 17'010	SFr. 8'505	No

Part Number	Description	Qty	MG Dis-count	List Price per part #	End-User MG Price* per part #	Last Order Date Soon?
SECPFEF3Z	Sun SPARC Enterprise T5120 Server, 8 Core 1.4GHz UltraSPARC T2 processor, 2nd Generation Chassis, 16GB FBDIMM memory (8 * 2GB), 2 * 146GB 10K RPM SAS disks, 1 SATA DVD+/-RW, 4 - 10/100/1000 Ethernet ports, 1 serial port, 4 USB ports,1 dedicated PCI-E low profile slot, 2 PCI-E low profile or XAUI (10Gb ethernet) slots, 2 (N+1) 720W power supplies, Solaris 10 pre-installed, RoHS-6 compliant.(Standard Configuration)	2	50%	SFr. 32'450	SFr. 16'225	No
SEDPADF1Z	Sun SPARC Enterprise T5220 Server, 4 Core 1.2GHz UltraSPARC T2 processor, 2nd Generation Chassis, 8GB FBDIMM memory (4 * 2GB), 2 * 146GB 10K RPM SAS disks, 1 SATA DVD+/-RW, 4 - 10/100/1000 Ethernet ports, 1 serial port, 4 USB ports,4 dedicated PCI-E low profile slots, 2 PCI-E low profile or XAUI (10Gb ethernet) slots, 2 (N+1) 750 W power supplies, Solaris 10 pre-installed, RoHS-6 compliant.(Standard Configuration)	2	50%	SFr. 19'690	SFr. 9'845	No
SEDPFFF1Z	Sun SPARC Enterprise T5220 Server, 8 Core 1.4GHz UltraSPARC T2 processor, 2nd Generation Chassis, 32GB FBDIMM memory (16 * 2GB), 2 * 146GB 10K RPM SAS disks, 1 SATA DVD+/-RW, 4 - 10/100/1000 Ethernet ports, 1 serial port, 4 USB ports,4 dedicated PCI-E low profile slot, 2 PCI-E low profile or XAUI (10Gb ethernet) slots, 2 (N+1) 750W power supplies, Solaris 10 pre-installed, RoHS-6 compliant.(Standard Configuration)	2	50%	SFr. 37'170	SFr. 18'585	No
SEDPGJF1Z	Sun SPARC Enterprise T5220 Server, 8 Core 1.6GHz UltraSPARC T2 processor, 2nd Generation Chassis, 64GB FBDIMM memory (16 * 4GB), 2 * 146GB 10K RPM SAS disks, 1 SATA DVD+/-RW, 4 - 10/100/1000 Ethernet ports, 1 serial port, 4 USB ports, 4 dedicated PCI-E low profile slot, 2 PCI-E low profile or XAUI (10Gb ethernet) slots, 2 (N+1) 750W power supplies, Solaris 10 pre-installed, RoHS-6 compliant.(Standard Configuration)	2	50%	SFr. 61'270	SFr. 30'635	No
Sun Sparc Enterprise T5140 / T5240 Server: PTO Configurations						
SETPBGE3Z	Sun SPARC Enterprise T5140 Server, 2x6 Core 1.2GHz UltraSPARC T2 Plus processors, 16GB FBDIMM memory (8x 2GB), 4 disk capacity, 2x146GB 10K RPM SAS disks, 1 DVD+/-RW, 4 10/100/1000 Ethernet ports, 1 serial port, 4 USB ports, 1 dedicated PCI-E low profile slot, 2 PCI-E low profile or XAUI (10Gb ethernet) slots, 2x(N+1) 760W power supplies, Solaris 10 software pre-installed, RoHS-6 complaint (Standard Configuration)	2	50%	SFr. 30'720	SFr. 15'360	No
SETPCJE4Z	Sun SPARC Enterprise T5140 Server, 2x8 Core 1.2GHz UltraSPARC T2 Plus processors, 32GB FBDIMM memory (16x 2GB), 8 disk capacity, 2x146GB 10K RPM SAS disks, 1 DVD+/-RW, 4 10/100/1000 Ethernet ports, 1 serial port, 4 USB ports, 1 dedicated PCI-E low profile slot, 2 PCI-E low profile or XAUI (10Gb ethernet) slots, 2x(N+1) 760W power supplies, Solaris 10 software pre-installed, RoHS-6 complaint (Standard Configuration)	2	50%	SFr. 45'990	SFr. 22'995	No
SEUPDJE1Z	Sun SPARC Enterprise T5240 Server, 2x8 Core 1.4GHz UltraSPARC T2 Plus processors, 32GB FBDIMM memory (16x 2GB), 8 disk capacity, 2x146GB 10K RPM SAS disks, 1 DVD+/-RW, 4 10/100/1000 Ethernet ports, 1 serial port, 4 USB ports, 4 dedicated PCI-E low profile slot, 2 PCI-E low profile or XAUI (10Gb ethernet) slots, 2x(N+1) 1100W power supplies, Solaris 10 software pre-installed, RoHS-6 complaint (Standard Configuration)	2	50%	SFr. 48'670	SFr. 24'335	No
SEUPDPE3Z	Sun SPARC Enterprise T5240 Server, 2x8 Core 1.4GHz UltraSPARC T2 Plus processors, 64GB FBDIMM memory (16x 4GB), 16 disk capacity, 2x146GB 10K RPM SAS disks, 1 DVD+/-RW, 4 10/100/1000 Ethernet ports, 1 serial port, 4 USB ports, 4 dedicated PCI-E low profile slot, 2 PCI-E low profile or XAUI (10Gb ethernet) slots, 2x(N+1) 1100W power supplies, Solaris 10 software pre-installed, this config.requires high-line(220V) power input. RoHS-6 complaint (Standard Configuration)	2	50%	SFr. 60'640	SFr. 30'320	No
SEUPEPE1Z	Sun SPARC Enterprise T5240 Server, 2x8 Core 1.6GHz UltraSPARC T2 Plus processors, 64GB FBDIMM memory (16x 4GB), 8 disk capacity, 2x146GB 10K RPM SAS disks, 1 DVD+/-RW, 4 10/100/1000 Ethernet ports, 1 serial port, 4 USB ports, 4 dedicated PCI-E low profile slot, 2 PCI-E low profile or XAUI (10Gb ethernet) slots, 2x(N+1) 1100W power supplies, Solaris 10 software pre-installed, RoHS-6 complaint (Standard Configuration)	2	50%	SFr. 75'290	SFr. 37'645	No
Sun Sparc Enterprise T5440 Server: PTO Configurations						
SEVPDJF2Z	Sun SPARC Enterprise T5440 server, 2 x 1.4 Ghz, 8 cores, 32 GB (16 x 2 GB) of memory at 667 Mhz, 2 x 146 GB SAS, 10,000 RPM HDD, 4 x 1120 watt PSU, Slim DVD RW, 2 memory expansion modules, Solaris 10 5/09 Preinstalled (Standard Configuration), RoHS-6 Compliant	2	50%	SFr. 53'710	SFr. 26'855	No
SEVPHSF2Z	Sun SPARC Enterprise T5440 server, 4 x 1.4 Ghz, 8 cores, 128 GB (32 x 4 GB) of memory at 667 Mhz, 2 x 146 GB SAS, 10,000 HDD, 4 x 1120 watt PSU, Slim DVD RW, 4 memory expansion modules, Solaris 10 5/09 Preinstalled (Standard Configuration), RoHS-6 Compliant	2	50%	SFr. 119'860	SFr. 59'930	No
SEVPJSF3Z	Sun SPARC Enterprise T5440 server, 4 x 1.6 Ghz, 8 cores, 128 GB (32 x 4 GB) of memory at 800 Mhz, 2 x 146 GB SAS, 10,000 HDD, 4 x 1120 watt PSU, Slim DVD RW, 4 memory expansion modules,Solaris 10 5/09 Preinstalled (Standard Configuration), RoHS-6 Compliant	2	50%	SFr. 154'350	SFr. 77'175	No
Sun Sparc Enterprise M3000 Server: PTO Configurations						
SEWPACA1Z	Sun SPARC Enterprise M3000 server. Includes 1, quad-core,2.52GHz SPARC64 VII Processor (1 CPU board with 1 CPU & 5MB on-chip L2 10-way cache), and 16GB system memory (1 memory module with 4*4GB DDR2 DIMMs), 2 * 146GB SAS hard disks, 1 DVD-ROM, 4*Gb ethernet ports, 1 I/O tray with 4 PCI-E slots, 2 power supplies (110V or 220V with 1N redundancy), RoHS-5.	2	50%	SFr. 34'650	SFr. 17'325	No
SEWPADA1Z	Sun SPARC Enterprise M3000 server. Includes 1, 4 core, 2.52GHz SPARC64 VII Processor (1 CPU board with 1, 4 core CPU & 5MB on-chip L2 10-way cache), and 32GB system memory (1 memory module with 4*8GB DDR2 DIMMs), 2 * 146GB SAS hard disks, 1 DVD-ROM, 4*Gb ethernet ports, 1 I/O tray with 4 PCI-E slots, 2 power supplies (110V or 220V with 1N redundancy), RoHS-5.	2	50%	SFr. 54'180	SFr. 27'090	No
Sun Sparc Enterprise M4000 Server: PTO Configurations						
SEEPACB2Z	Sun SPARC Enterprise M4000 server. Includes 2*2.15GHz SPARC64 VI Processors (1 CPU boards with 2 *CPUS each & 5MB on-chip L2 cache), and 32GB system memory on (2 memory modules with 8 * 2GB 1 rank DDR2 DIMMs), 2 * 146GB SAS hard disks, 1 DVD-ROM, 2*Gb ethernet ports, 1 I/O tray with 4 PCI-E and 1 PCI-X slots, 2 power supplies (220V with N+N redundancy or 110V), RoHS-5.	2	50%	SFr. 52'450	SFr. 26'225	No
SEEPDCB2Z	Sun SPARC Enterprise M4000 server. Includes 2*2.4GHz SPARC64 VII four-core Processors (1 CPU boards with 2 *CPUS each & 5MB on-chip L2 cache), and 32GB system memory on (2 memory modules with 8 * 2GB 1 rank DDR2 DIMMs), 2 * 146GB SAS hard disks, 1 DVD-ROM, 2*Gb ethernet ports, 1 I/O tray with 4 PCI-E and 1 PCI-X slots, 2 power supplies (220V with N+N redundancy or 110V), RoHS-5.	2	50%	SFr. 60'010	SFr. 30'005	No
SEEPBCB2Z	Sun SPARC Enterprise M4000 server. Includes 4*2.15GHz SPARC64 VI Processors (2 CPU boards with 2 *CPUS each & 5MB on-chip L2 cache), and 32GB system memory (2 memory modules with 8 * 2GB 1 rank DDR2 DIMMs), 2 * 146GB SAS hard disks, 1 DVD-ROM, 2*Gb ethernet ports, 1 I/O tray with 4 PCI-E and 1 PCI-X slots, 2 power supplies (220V with N+N redundancy or 110V), RoHS-5.	2	50%	SFr. 77'650	SFr. 38'825	No
SEEPCEB2Z	Sun SPARC Enterprise M4000 server. Includes 4*2.4GHz SPARC64 VII four-core Processors (2 CPU boards with 2 *CPUS each & 5MB on-chip L2 cache), and 32GB system memory on (2 memory modules with 8 * 2GB 1 rank DDR2 DIMMs), 2 * 146GB SAS hard disks, 1 DVD-ROM, 2*Gb ethernet ports, 1 I/O tray with 4 PCI-E and 1 PCI-X slots, 2 power supplies (220V with N+N redundancy or 110V), RoHS-5.	2	50%	SFr. 92'770	SFr. 46'385	No

Part Number	Description	Qty	MG Dis-count	List Price per part #	End-User MG Price* per part #	Last Order Date Soon?
SEEPAKB2Z	Sun SPARC Enterprise M4000 Server, 2.15 GHz SPARC64 VI Dual-Core Processors (1 CPU Board with 2 CPUS Each and 5MB On-Chip L2 Cache), and 16 GB System Memory on 2 Memory Modules (2 Memory Modules with 4 x 2 GB Single Rank DDR2 DIMMs), 2 x 146 GB SAS Disk Drives, 1 DVD-ROM, 2 Gb Ethernet Ports, 1 I/O Tray with 4 PCIe and 1 PCI-X Slots, 2 Power Supplies (220V with N+N Redundancy or 110V), RoHS-5 Compliant	2	50%	SFr. 41'270	SFr. 20'635	No
SEEPDKB2Z	Sun SPARC Enterprise M4000 Server, 2.4 GHz SPARC64 VII Quad-Core Processors (1 CPU Board with 2 CPUS Each and 5MB On-Chip L2 Cache), and 16 GB System Memory (2 Memory Modules with 4 x 2 GB Single Rank DDR2 DIMMs), 2 x 146 GB SAS Disk Drives, 1 DVD-ROM, 2 Gb Ethernet Ports, 1 I/O tray with 4 PCIe and 1 PCI-X Slots, 2 Power Supplies (110V or 220V with N+N redundancy), RoHS-5 Compliant	2	50%	SFr. 48'830	SFr. 24'415	No
Sun Sparc Enterprise M5000 Server: PTO Configurations						
SEFPBCC2Z	Sun SPARC Enterprise M5000 server. Includes 4*2.15GHz SPARC64 VI Processors (2 CPU boards with 2 *CPUS each & 5MB on-chip L2 cache), and 32GB system memory (2 memory modules with 8 * 2GB 1 rank DDR2 DIMMs), 2 * 146GB SAS hard disks, 1 DVD-ROM, 2*Gb ethernet ports, 1 I/O tray with 4 PCI-E and 1 PCI-X slots, 4 power supplies (220V with N+N redundancy or 110V), RoHS-5.	2	50%	SFr. 99'390	SFr. 49'695	No
SEFPECC2Z	Sun SPARC Enterprise M5000 server. Includes 4*2.4GHz SPARC64 VII four-core Processors (2 CPU boards with 2 *CPUS each & 5MB on-chip L2 cache), and 32GB system memory (2 memory modules with 8 * 2GB 1 rank DDR2 DIMMs), 2 * 146GB SAS hard disks, 1 DVD-ROM, 2*Gb ethernet ports, 1 I/O tray with 4 PCI-E and 1 PCI-X slots, 4 power supplies (220V with N+N redundancy or 110V), RoHS-5.	2	50%	SFr. 114'350	SFr. 57'175	No
SECPADF1Z	Sun SPARC Enterprise T5120 Server, 4 Core 1.2GHz UltraSPARC T2 processor, 2nd Generation Chassis, 8GB FBDIMM memory (4 * 2GB), 2 * 146GB 10K RPM SAS disks, 1 SATA DVD+/-RW, 4 10/100/1000 Ethernet ports, 1 serial port, 4 USB ports, 1 dedicated PCI-E low profile slot, 2 PCI-E low profile or XAUI (10Gb ethernet) slots, 2 (N+1) 720W power supplies, Solaris 10 pre-installed, RoHS-6 compliant.(Standard Configuration)	2	50%	SFr. 17'010	SFr. 8'505	No
SEFPFDD2Z	Sun SPARC Enterprise M5000 server. Includes 8*2.4GHz SPARC64 VII four-core Processors (4 CPU boards with 2 *CPUS each & 5MB on-chip L2 cache), and 64GB system memory (4 memory modules with 8 * 2GB 1 rank DDR2 DIMMs), 4 * 146GB SAS hard disks, 1 DVD-ROM, 4*Gb ethernet ports, 2 I/O trays with 4 PCI-E and 1 PCI-X slots, 4 power supplies (220V with N+N redundancy or 110V), RoHS-5.	2	50%	SFr. 208'690	SFr. 104'345	No
SEFPAKC2Z	Sun SPARC Enterprise M5000 Server, 2.15 GHz SPARC64 VI Dual-Core Processors (1 CPU Board with 2 CPUS Each and 5MB On-Chip L2 Cache), and 16 GB System Memory on 2 Memory Modules (2 Memory Modules with 4 x 2 GB Single Rank DDR2 DIMMs), 2 x 146 GB SAS Disk Drives, 1 DVD-ROM, 2 Gb Ethernet Ports, 1 I/O Tray with 4 PCIe and 1 PCI-X Slots, 4 Power Supplies (220V with N+N Redundancy or 110V), RoHS-5 Compliant	2	50%	SFr. 63'000	SFr. 31'500	No
SEFPDKC2Z	Sun SPARC Enterprise M5000 Server, 2.4 GHz SPARC64 VII Quad-Core Processors (1 CPU Board with 2 CPUS Each and 5MB On-Chip L2 Cache), and 16 GB System Memory (2 Memory Modules with 4 x 2 GB Single Rank DDR2 DIMMs), 2 x 146 GB SAS Disk Drives, 1 DVD-ROM, 2 Gb Ethernet Ports, 1 I/O tray with 4 PCIe and 1 PCI-X Slots, 4 Power Supplies (110V or 220V with N+N redundancy), RoHS-5 Compliant	2	50%	SFr. 70'560	SFr. 35'280	No
SUN BLADE 6000 SERVER MODULES						
Sun Blade 6000 Server Module Base Chassis + NEMs (Mandatory for Sun Blade X64 Systems)						
A90-B	1 Sun Blade 6000 Chassis with Generation 2 midplane, 10U, 2x 6000W power supply modules, 6 redundant rear fan modules, 1 Chassis Monitoring Module, Rack Mount Rail Kit, Accessory Kit with Dongle and RJ45-DB9 adapter, 9 server module filler panels, 20 PCIe ExpressModule filler panels, 2 Network Express Module filler panels, Standard Configuration, RoHS-5 Compliant.	2	50%	SFr. 8'670	SFr. 4'335	No
X5076A-Z	PWR CORD, QTY 4, AC INPUT, 20A (IEC 320-C19 to IEC 320-C20, 1.5 M) Optional cords for connecting a rack mounted Sun Blade Modular System chassis to a Modular Power System (MPS). RoHS-6.	2	50%	SFr. 58	SFr. 29	No
X4238	Sun Blade 6000 Virtualized NEM 10-port 1GbE + 4-port SAS + 2 port 10GbE, RoHS-5 compliant, Xoption	4	50%	SFr. 5'750	SFr. 2'875	No
X5561A-Z	Sun 10 Gigabit Ethernet SFP+ Short Reach Pluggable Transceiver. RoHS-5. X-Option.	4	50%	SFr. 400	SFr. 200	No
Sun Blade 6000 Network X Options: Express Modules						
X7283A-Z	Sun PCI-E Express Dual Port Gigabit Ethernet MMF (fiber) ExpressModule RoHS-6 compliant	2	50%	SFr. 1'250	SFr. 625	No
X7284A-Z	Sun x4 PCI-Express Quad Gigabit Ethernet UTP ExpressModule, OEM from Intel,RoHS-6	2	50%	SFr. 920	SFr. 460	No
X7287A-Z	Sun Quad Gigabit Ethernet UTP x8 PCIe ExpressModule using Sun Neptune chip. RoHS-6 compliant	2	50%	SFr. 920	SFr. 460	No
SG-XPCIE2FCGBE-Q-Z	Sun StorageTek Dual 4Gb FC Dual GbE HBA in ExpressModule form factor, RoHS-6 compliant, Qlogic. X-Option.	2	50%	SFr. 2'210	SFr. 1'105	No
SG-XPCIE2FCGBE-E-Z	Sun StorageTek Dual 4Gb FC Dual GbE HBA in ExpressModule form factor, RoHS-6 compliant, Emulex. X-Option.	2	50%	SFr. 2'050	SFr. 1'025	No
X1028A-Z	Sun Dual 10GbE XFP PCIe ExpressModule for Sun Blade Servers	2	50%	SFr. 1'390	SFr. 695	No
SG-XPCIE2FC-QB4-Z	Sun Storagetek PCIe Enterprise 4Gb FC Host Bus Adapter (QLogic), ExpressModule Form Factor, Dual Port, RoHS 6 compliant	2	50%	SFr. 1'970	SFr. 985	No
SG-XPCIE2FC-EB4-Z	Sun Storagetek PCI-E Enterprise 4Gb FC Host Bus Adapter (Emulex), ExpressModule Form Factor, Dual Port, RoHS 6 compliant	2	50%	SFr. 1'970	SFr. 985	No
SG-XPCIE8SAS-EB-Z	Sun Storagetek (TM) SAS Host Bus Adapter, ExpressModule form factor, Eight Port, RoHS 6 compliant	2	50%	SFr. 780	SFr. 390	No
Sun Blade X6240 Server Modules: ATO Options to be combined with Sun Blade 6000 Server Module Base Chassis + NEMs						
4261A	4 GB Memory kit DDR2_667 Registered ECC DIMMs (2x2GB) for Sun Blade X6240 and X6440 Server Modules requiring single rank DIMMs. RoHS-5. ATO & Factory Integration.	2	50%	SFr. 300	SFr. 150	No
4262A	8 GB Memory kit DDR2_667 Registered ECC DIMMs (2x4GB) for Sun Blade X6240 and X6440 Server Modules requiring dual rank DIMMs. RoHS-5. ATO & Factory Integration.	2	50%	SFr. 540	SFr. 270	No
4680A	16 GB Compact Flash Card; Used for flash based booting and OS image pre-loads. RoHS 5. For ATO and Factory Integration.	2	50%	SFr. 810	SFr. 405	No
RA-SS2CF-300G10K	300GB 10K RPM 2.5" SAS hard disk drive with Marlin bracket. Factory Integrated. RoHS-6	2	50%	SFr. 1'010	SFr. 505	No
RA-ST2CF-32G2SSD	2.5" 32GB SATA SSD (Type: SLC) with Marlin bracket, RoHS-6 Compliant. For Factory Integration Only	2	50%	SFr. 1'740	SFr. 870	No
RB-SS2CD-146G10K	146GB 10K RPM 2.5" SAS hard disk drive with Nemo bracket. RoHS-6 Compliant. (ATO)	2	50%	SFr. 490	SFr. 245	No
Sun Blade X6270 Server Modules: ATO Options to be combined with Sun Blade 6000 Server Module Base Chassis + NEMs						
4650A	Sun Blade X6270 Server Module 2GB (1x2GB) Memory Kit, DDR3 1066MHz Registered ECC DIMM, Factory Integration, RoHS-6 Compliant.	2	50%	SFr. 141	SFr. 71	No
4680A	16 GB Compact Flash Card; Used for flash based booting and OS image pre-loads. RoHS 5. For ATO and Factory Integration.	2	50%	SFr. 810	SFr. 405	No

Part Number	Description	Qty	MG Dis-count	List Price per part #	End-User MG Price* per part #	Last Order Date Soon?
RA-ST2CF-32G2SSD	2.5" 32GB SATA SSD (Type: SLC) with Marlin bracket, RoHS-6 Compliant. For Factory Integration Only	2	50%	SFr. 1'740	SFr. 870	No
RA-SS2CF-300G10K	300GB 10K RPM 2.5" SAS hard disk drive with Marlin bracket. Factory Integrated. RoHS-6	2	50%	SFr. 1'010	SFr. 505	No
RB-SS2CF-146G10K	146GB 10K RPM 2.5" SAS hard disk drive with Marlin bracket. RoHS-6. (ATO)	2	50%	SFr. 490	SFr. 245	No
Sun Blade X6275 Server Modules: ATO Options to be combined with Sun Blade 6000 Server Module Base Chassis + NEMs						
4672A	8GB DDR3 Memory Kit 1x8GB 1066MHz DIMM For Sun Blade X6275 Server Module, ROHS-5. For Factory Integration.	2	50%	SFr. 1'410	SFr. 705	No
4676A	Sun Flash Module Kit, 2x 24GB SATA-based Sun Flash Modules for Sun Blade X6275 Server Module, Factory Integration, RoHS-6 Compliant.	2	50%	SFr. 2'370	SFr. 1'185	No
Sun Blade X6440 Server Modules: ATO Options to be combined with Sun Blade 6000 Server Module Base Chassis + NEMs						
4261A	4 GB Memory kit DDR2_667 Registered ECC DIMMs (2x2GB) for Sun Blade X6240 and X6440 Server Modules requiring single rank DIMMs. RoHS-5. ATO & Factory Integration.	2	50%	SFr. 300	SFr. 150	No
4262A	8 GB Memory kit DDR2_667 Registered ECC DIMMs (2x4GB) for Sun Blade X6240 and X6440 Server Modules requiring dual rank DIMMs. RoHS-5. ATO & Factory Integration.	2	50%	SFr. 540	SFr. 270	No
4680A	16 GB Compact Flash Card; Used for flash based booting and OS image pre-loads. RoHS 5. For ATO and Factory Integration.	2	50%	SFr. 810	SFr. 405	No
4249A	16 GB Memory kit DDR2-667 Registered ECC DIMMs (2x 8GB Dual Rank) for Sun Blade X6240 and X6440 Server Modules requiring dual rank DIMMs. RoHS-5. ATO & Factory Integration.	2	50%	SFr. 3'310	SFr. 1'655	No
4249A	16 GB Memory kit DDR2-667 Registered ECC DIMMs (2x 8GB Dual Rank) for Sun Blade X6240 and X6440 Server Modules requiring dual rank DIMMs. RoHS-5. ATO & Factory Integration.	2	50%	SFr. 3'310	SFr. 1'655	No
SUN STORAGE TEK **						
Sun Storage Tek 25xx Array						
XTA2501R01A1N5000	Sun StorageTek(TM) 2501 SAS Expansion Array, Rack-Ready Expansion Tray, 5TB, 5 * 1TB 7.2Krpm SATA-II drives, 1 * SAS I/O module, 2 * redundant AC power supplies and 2 * redundant cooling fans; Includes 1 * 1m SAS host cable; RoHS-5	2	50%	SFr. 8'510	SFr. 4'255	No
XTA2501R01A2F3600	Sun StorageTek(TM) 2501 SAS Expansion Array, Rack-Ready Expansion Tray, 3600GB, 12 * 300GB 15Krpm SAS drives, 2 * SAS I/O modules, 2 * redundant AC power supplies and 2 * redundant cooling fans; Includes 2 * 1m SAS host cables; RoHS-5	2	50%	SFr. 14'810	SFr. 7'405	No
XTA2530R01A2A6000	Sun StorageTek(TM) 2530 SAS Array, Rack-Ready Controller Tray, 6000GB, 12 * 500GB 7.2Krpm SATA-II drives, 2 * 512MB cache SAS HW RAID controllers, 2 * redundant AC power supplies, 2 * redundant cooling fans; Includes Sun StorageTek(TM) Common Array Manager software and 2 * storage domains using Sun StorageTek(TM) Storage Domains software; RoHS-5	2	50%	SFr. 13'860	SFr. 6'930	No
XTA2530R01A2F1500	Sun StorageTek(TM) 2530 SAS Array, Rack-Ready Controller Tray, 1500GB, 5 * 300GB 15Krpm SAS drives, 2 * 512MB cache SAS HW RAID controllers, 2 * redundant AC power supplies, 2 * redundant cooling fans; Includes Sun StorageTek(TM) Common Array Manager software and 2 * storage domains using Sun StorageTek(TM) Storage Domains software; RoHS-5	2	50%	SFr. 12'760	SFr. 6'380	No
XTA2540R01A1N5000	Sun StorageTek(TM) 2540 FC Array, Rack-Ready Controller Tray, 5TB, 5 * 1TB 7.2Krpm SATA-II drives, 1 * 512MB cache FC HW RAID controller, 2 * redundant AC power supplies, 2 * redundant cooling fans, and 2 * shortwave SFPs; Includes Sun StorageTek(TM) Common Array Manager software and 2 * storage domains using Sun StorageTek(TM) Storage Domains software; RoHS-5	2	50%	SFr. 11'340	SFr. 5'670	No
XTA2540R01A2A6000	Sun StorageTek(TM) 2540 FC Array, Rack-Ready Controller Tray, 6000GB, 12 * 500GB 7.2Krpm SATA-II drives, 2 * 512MB cache FC HW RAID controllers, 2 * redundant AC power supplies, 2 * redundant cooling fans, and 4 * shortwave SFPs; Includes Sun StorageTek(TM) Common Array Manager software and 2 * storage domains using Sun StorageTek(TM) Storage Domains software; RoHS-5	2	50%	SFr. 14'810	SFr. 7'405	No
XTA2540R01A2F3600	Sun StorageTek(TM) 2540 FC Array, Rack-Ready Controller Tray, 3600GB, 12 * 300GB 15Krpm SAS drives, 2 * 512MB cache FC HW RAID controllers, 2 * redundant AC power supplies, 2 * redundant cooling fans, 4 * shortwave SFPs; Includes Sun StorageTek(TM) Common Array Manager software and 2 * storage domains using Sun StorageTek(TM) Storage Domains software; RoHS-5	2	50%	SFr. 20'160	SFr. 10'080	No
XTA2540R01A2N12000	Sun StorageTek(TM) 2540 FC Array, Rack-Ready Controller Tray, 12TB, 12 * 1TB 7.2Krpm SATA-II drives, 2 * 512MB cache FC HW RAID controllers, 2 * redundant AC power supplies, 2 * redundant cooling fans, and 4 * shortwave SFPs; Includes Sun StorageTek(TM) Common Array Manager software and 2 * storage domains using Sun StorageTek(TM) Storage Domains software; RoHS-5	2	50%	SFr. 22'050	SFr. 11'025	No
Sun Storage 7000 Unified Systems						
XTA7110-14ASA20	Sun Storage 7110 Unified Storage System: 2TB raw, 16x146GB 2.5 SAS HDD, 8GB RAM, 1x1.9GHz Quad-Core processor, 4x 10/100/1000 Ethernet ports. Rail kit included. No Power Cord, order Geo-specific X-option. RoHS 5.	2	50%	SFr. 15'440	SFr. 7'720	No
XTA7210-24AS18N22	Sun Storage 7210 Unified Storage System: 22.5TB raw, 47x500GB 3.5 SATA HDD, 64GB RAM, 1x18GB Logzilla Flash Accelerator, 2x2.3GHz Quad-Core processor, 4x 10/100/1000 Ethernet ports. Includes Slide Rail Kit and Cable Management Arm. No Power Cord, order Geo-specific X-option. RoHS 5.	2	50%	SFr. 100'650	SFr. 50'325	No
XTA7210-24AS36N44	Sun Storage 7210 Unified Storage System: 44TB raw, 46x1TB 3.5 SATA HDD, 64GB RAM, 2x18GB Logzilla Flash Accelerator, 2x2.3GHz Quad-Core processor, 4x 10/100/1000 Ethernet ports. Includes Slide Rail Kit and Cable Management Arm. No Power Cord, order Geo-specific X-option. RoHS 5.	2	50%	SFr. 164'910	SFr. 82'455	No
XTA7210-24AS00N23	Sun Storage 7210 Unified Storage System: 23TB raw, 48x500GB 3.5" SATA HDD, 64GB RAM, 2x2.3GHz Quad-Core processor, 4x 10/100/1000 Ethernet ports. Includes Slide Rail Kit and Cable Management Arm. No Power Cord, order Geo-specific X-option. RoHS 5.	2	50%	SFr. 90'090	SFr. 45'045	No
XTA7210-24AS00N46	Sun Storage 7210 Unified Storage System: 46TB raw, 48x1TB 3.5" SATA HDD, 64GB RAM, 2x2.3GHz Quad-Core processor, 4x 10/100/1000 Ethernet ports. Includes Slide Rail Kit and Cable Management Arm. No Power Cord, order Geo-specific X-option. RoHS 5.	2	50%	SFr. 143'960	SFr. 71'980	No

* "Free" = Buy 1 Get 1 Free = Buy 2 at 50% discount of List Price for each item

* Matching Grant Program valid from 09OCT09 till 20DEC09 and in Europe, Middle East and Africa only

* PLEASE CHECK YOUR LOCAL PRICE LIST FOR AVAILABILITY AND PRICING OF THESE CONFIGURATIONS IN YOUR COUNTRY

* Prices are net, VAT and Customs Duties to be added

* Sun disclaims any responsibility for inaccuracies or typographical errors

* Click [here](#) for more information